



Open Front Cover



Hinged Cover

Applications:

Added environmental protection for Cooper Crouse-Hinds control stations is now available from a patented "slip on" series of covers. Easy to install, these enclosures are available in hinged and open front styles, and are ideal for corrosive and adverse areas where product endurance is essential.

Secured Access Hinged Cover

- High moisture areas due to weather, steam, or wash down procedures.
- Areas where dirt, dust, mud, sand, etc. interferes with equipment operation.
- Prevention of accidental equipment operation.
- Instances requiring equipment lock out/tag out.

Quick Access Open Front Cover

- Areas requiring quick access to control device.
- Areas of high moisture from weather or dripping liquid.
- Prevention of accidental equipment operation.
- Areas with possible damage from bumping or banging.

Features and Benefits:

- Clear UV stabilized Lexan polycarbonate plastic allows the end-user to see enclosed controls and is strong enough to withstand the rough treatment found in the industrial work place.
- Downtime due to weather or accidental bumping is eliminated and plant shutdowns caused by inoperable or accidentally operated pushbutton devices are non-existent.
- Lock out/tag out capabilities conform to OSHA requirements and provides increased personnel safety.
- Quick and easy slip on installation requires no tools or interruption of service.
- Hinged cover provides superior sealing through heavy-duty neoprene gaskets.
- Colored covers are available (e.g. red for emergency, yellow for fire alarm, etc.).
- Specific chemical resistant covers available (may not be clear) - consult factory for minimum order quantity.
- Capability to engineer cover to fit any size device - consult factory.



Hinged Covers

Single Gang Application

EDS(C) and EFD(C) control stations
 EFS(C) control stations
 MC(C) control stations
 FS(C) back box with cover assembly
 FD(C) back box with cover assembly
 EGF11 and EGF12 (Ground Fault)
 N2S(C) Krydon: 1 & 2 devices
 N2D(C) Krydon: 1 & 2 devices
 GHG432 control station

Cat.

NC CH1
 NC CH1 EFS
 NC CH1 MC
 NC CH1 FS
 NC CH1 FD
 NC CH1 EGF 11
 NC CH1 N2S
 NC CH1 N2D
 NC CH1 GHG

Single Gang (Long) Application

EFD(C) (3 device)
 N2S(C) Krydon: 3 devices
 N2S(C) Krydon: 4 devices

Cat.

NC CH1 3L
 NC CH1 N2S 3L
 NC CH1 N2S 4L

Double Gang Application

EDS(C) control stations
 EDSCM32: 2 gang tandem
 EDSCM33: 3 gang tandem
 FS(C) back box with cover
 FD(C) back box with cover
 EDSC378 - 3 gang tandem assembly

Cat.

NC CH2
 NC CH2L
 NC CH3L
 NC CH2 FS
 NC CH2 FD
 NC CH1 MC3

Open Front Covers

Single Gang Application

EDS(C) and EFD(C) control stations
 EFS(C) control stations
 MC(C) control stations
 FS(C) back box with cover assembly
 FD(C) back box with cover assembly
 EGF11 and EGF12 (Ground Fault)
 N2S(C) Krydon: 2 device assembly
 N2D(C) Krydon: 3 device assembly

Cat.

NC CH1 QA
 NC CH1 EFS QA
 NC CH1 MC QA
 NC CH1 FS QA
 NC CH1 FD QA
 NC CH1 EGF QA
 NC CH1 N2S QA
 NC CH1 N2D QA

Single Gang (Long) Application

EFD(C): 3 device control stations
 N2S(C) Krydon: 3 device assembly
 N2S(C) Krydon: 4 device assembly

Cat.

NC CH1 3L QA
 NC CH1 N2S 3L QA
 NC CH1 N2S 4L QA

Double Gang Application

EDS(C) control stations
 EDSCM32: 2 gang tandem
 EDSCM 33: 3 gang tandem
 FS(C) back box with cover assembly
 FD(C) back box with cover assembly

Cat.

NC CH2 QA
 NC CH2L QA
 NC CH3L QA
 NC CH2 FS QA
 NC CH2 FD QA

Custom covers can be supplied but must be accompanied by either a sample of the device to be covered or a copy of a drawing with all actual measurements of the device to be covered. Covers can also be color-coded. Consult factory.