



NORMA DE FABRICACION: UNE / ASTM

ACABADO	Galvanizado en caliente ASTM A-153						
MATERIAL	Acero de alta resistencia						
M1AM0012	1/2"	3.50	1270 mm	6	B	50 KN	Azul
D1AM0009	11.2±0.5	2.55	880 mm	6	A	40 KN	Naranja
D1AM0012	18.1±0.5	4.20	880 mm	7	A	50 KN	Blanco
D1AM0008	16.2±0.5	2.55	880 mm	9	A	50 KN	Verde
D1AM0004	1/4"	2.10	700 mm	5	A	8 KN	Amarillo
D1AM0003	3/16"	2.10	520 mm	4	A	8 KN	Rojo
D1AM0002	1/2"	2.55	1030 mm	7	A	50 KN	Azul
D1AM0006	1/2"	2.55	1245 mm	7	A	50 KN	Azul
D1AM0001	3/8"	2.55	890 mm	6	A	30 KN	Naranja
D1AM0010	1/2"	2.55	965 mm	7	B	50 KN	Verde
D1AM0000	5/16"	2.55	787 mm	5	A	20 KN	Negro
CODIGO	DIAMETRO DEL CONDUCTOR	DIAMETRO DEL ALAMBRE	LONGITUD	N° DE HILOS	CLASE	CARGA MINIMA DESLIZAM.	COLOR



EMPRESA:



CORPELIMA

Importadores y Líderes en Soluciones Eléctricas

FECHA:

08/03/19

ESCALA:

S/E

AMARRE
PREFORMADO
DE F°G°

LAMINA N°:

20-A-FO

DIBUJADO
POR:

J.P