



INSULATED RESCUE HOOK - Salisbury's insulated rescue hook is an invaluable tool for any workplace. It is used to release a victim from contact. Confined spaces, in vaults, or just near electrical cabinets and switch gear are some of the places where this tool is a must. Insulated rescue hooks feature a foam-filled, fiberglass reinforced handle for superior electrical insulation and a coated, heat treated body hook with an 18" opening and are made in accordance with ASTM Standard F711. The stick is available in the standard lengths of 6 and 8 feet. Other lengths are available as a special order. Contact us with your requirements.

STATIC DISCHARGE STICK - The Static Discharge Stick is designed to safely remove the static charge after de-energizing. This tool is pre-assembled and includes a brass alloy "U" hook, closed cell foam-filled tubular fiberglass switch stick made in accordance with ASTM Standard F711. Static discharge sticks have 6 feet of copper grounding cable attached to a Salisbury 1814 flat jaw, grade 3, bronze serrated clamp with strain relief.

CAT. NO.	DESCRIPTION / ft. (m)	WEIGHT lbs. (kgs)
INSULATED RESCUE HOOK		
24400	Rescue Hook 3' (0.9 m) length	3.4 (1.5)
24401	Rescue Hook 6' (1.8 m) length	4.5 (2)
24403	Rescue Hook 8' (2.4 m) length	5.5 (2.5)

STATIC DISCHARGE STICK		
20817	Static Discharge Stick OAL 3'8" (1.08 m) length	8 (3.6)
22629	Static Discharge Stick w/ Universal Attachment 1' (0.3 m) length	.38 (0.17)



WARNING: DISCHARGE STICKS ARE NOT GROUNDING TOOLS AS DESCRIBED BY OSHA 1910.269 AND CARRY NO FAULT DUTY RATING.

